



Bombardier Recreational Products Inc.
10101 Science Drive
Sturtevant, WI 52177
www.evinrude.com

MirroCraft

Mirrocraft Boats
39 N Harding Ave
Gillett, WI 54124
920-855-2168 / Fax 920-855-6537
www.mirrocraft.com

2010 Mirrocraft 1685 Troller EXP



BOAT	
2010 Mirrocraft 1685 Troller EXP	
Material:	Aluminum
Length:	16' 9"
Beam:	85"
Weight w/o Engine:	960 LBS Dry
Maximum HP:	90 HP
Fuel Capacity:	29 Gallons
Transom Height:	20" Shaft
Steering:	Cable

ENGINE	
2010 Evinrude® 60HP ETEC®	
Engine Type:	In Line 2 Cyl.
Horsepower:	60HP @ 5750 RPM
Displacement:	52.7 Cu. In.
Induction:	ETEC DFI
Operating Range:	5500-6000 RPM
Weight:	240 LBS Dry Weight
Gear Ratio:	2.67:1

PROPELLER	
BRP Viper™	
Material:	Stainless Steel
Diameter/Pitch:	13 3/4" x 17"
No. of Blades:	3
Part Number:	763930
MOUNTING HEIGHT	
Hole Position:	#1
Jack Plate:	N/A
Motor Height:	N/A

PERFORMANCE DATA				
RPM	MPH	GPH	MPG	RANGE
850	2.9	0.10	29.4	766
1000	3.5	0.10	35.3	921
1500	5.1	0.39	13.1	342
2000	6.3	0.60	10.5	274
2500	7.2	1.13	6.4	167
3000	9.5	1.85	5.1	134
3500	15.7	2.10	7.5	196
4000	20.0	2.45	8.2	213
4500	23.4	2.86	8.2	214
5000	26.9	3.07	8.8	228
5500	29.7	3.83	7.8	203
5800	32.0	5.20	6.2	161
Range (Miles) Based On 90% Fuel Capacity				

TEST CONDITIONS	
Water Conditions:	Light Chop
Wind Velocity:	5 MPH
Air Temperature:	50° F
Fuel Load:	6 Gal
Weight:	2 Men, Fuel, test & safety gear

PERFORMANCE SUMMARY	
Top Speed:	32.0 MPH
Best Fuel Efficiency:	8.8 MPG with a range of 228 Miles @ 26.9 MPH
Acceleration:	3.5 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.
© 2009 BRP US Inc. All rights reserved.

™ and the BPR logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

